



- 1-Water draining gutter FAKRO
- 2-Polyurethane insulating wedge
- 3-Tile supporting profile
- 4-XDP FAKRO vapour permeable collar
- 5-Tress made of sheep wool FAKRO (XDP)
- 6-Blocks made of sheep wool FAKRO (XDP)
- 17-Rafter
- 38-Installation bracket
- 57-Vertical joining gutter
- 109-XDS air-tight flashing FAKRO
- 370-KHV-AT THERMO FAKRO flashing upper element
- 371-KHV-AT THERMO FAKRO flashing lower element
- 372-KHV-AT THERMO FAKRO flashing side element
- 373-Thermal insulation of flashing KHV-AT THERMO FAKRO
- 677-FTP-V P5 pivot window FAKRO

FTP-V P5		
Frame width S[mm]	Frame height H[mm]	Window symbol
457	601	
	781	46
	981	48
	1181	
477	1401	
	601	
	781	47
	981	49
547	1181	
	1401	
	601	
	781	01
657	981	02
	1181	16
	1401	
	601	32
777	781	22
	981	03
	1181	04
	1401	14
937	601	33
	781	23
	981	05
	1181	06
1137	1401	07
	601	34
	781	24
	981	15
1337	1181	08
	1401	09
	601	35
	781	25
	981	20
	1181	10
	1401	11
	601	36
	781	26
	981	12
	1181	18

	Vertical and horizontal cross-section: FTP-V P5 roof window with KHV-AT THERMO flashing for high-profiled roofing materials - B2/1 combination				FORMAT: A3

Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality on the roof. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.